



Features

1000 TR

| Core thickness (mm) | U-value (W/m ² .K) | R-value (h.ft ² .°F/BTU) | Weight (kg/m ²)* |
|---------------------|-------------------------------|-------------------------------------|------------------------------|
| 30 mm | 2.70 | 2.10 | 5.00 |
| 40 mm | 2.70 | 2.10 | 5.00 |
| 50 mm | 2.70 | 2.10 | 5.00 |
| 60 mm | 2.70 | 2.10 | 5.00 |
| 80 mm | 2.70 | 2.10 | 5.00 |

1000 GL

| Core thickness (mm) | U-value (W/m ² .K) | R-value (h.ft ² .°F/BTU) | Weight (kg/m ²)* |
|---------------------|-------------------------------|-------------------------------------|------------------------------|
| 31 mm | 2.70 | 2.10 | 5.00 |
| 43 mm | 2.70 | 2.10 | 5.00 |
| 60 mm | 2.70 | 2.10 | 5.00 |
| 80 mm | 2.70 | 2.10 | 5.00 |



Standard Configuration

| | |
|------------------|--|
| Cover width: | 1000 mm |
| Material: | Single polycarbonate outside and double polycarbonate inside |
| Profiling: | TR or GL |
| Colours: | Blue transparent or crystal clear |
| Permeability: | Light 74% |
| Light diffusion: | 95% |
| Minimum length: | 500 mm |
| Maximum length: | 7000 mm |
| UV Barrier: | Topsheet is UV protected |



WWW.FALKPANELS.CA